
1 agc 1 U1 2



(11) Publication number: 200

Generated Document.

## PATENT ABSTRACTS OF JAPAN

(21) Application number: **11192469** 

(51) Intl. Cl.: G11B 5/31 G11B 5/02 G11B

(22) Application date: **07.07.99** 

(30) Priority:

(43) Date of application

26.01.01

publication:

(84) Designated contracting states:

(74) Representative:

(71) Applicant: NEC CORP

(72) Inventor: ISHI TSUTOMU

(54)**MAGNETORESISTANCE EFFECT COMPOSITE** HEAD, MAGNETIC **MEMORY DEVICE** EMPLOYING THE SAME, AND MANUFACTURE OF **MAGNETORESISTANCE** EFFECT COMPOSITE HEAD

(57) Abstract:

PROBLEM TO BE SOLVED: To obtain a magnetoresistance effect composite head which can pre scribe a narrow magnetic pole with a writing width of not wider than 0.5 µm with a necessary and sufficient machinning dimension tolerance.

SOLUTION: The magnetoresistance effect composite head comprises a magnetoresistance effect element 3 consisting of a spin valve element, an electrode part 5 adjacent to the element 3 and supplying a sensing current and 1st and 2nd magnetic shields 1 and 6 which hold the element 3 and the electrode part 5

200102311/A 1age 2 01 2

between them with reading gaps 2a and 2b therebetween. The 2nd magnetic shield 6 is used as a 1st magnetic pole, and a writing magnetic gap 7, a coil (9), coil insulation parts (10a) and (10b), a 2nd magnetic pole 8 and a protective film 11 are formed on the 2nd magnetic shield 6 to compose an inductive head.

COPYRIGHT: (C)2001, JPO

(a)

